



EURO LOCKSHIELD

The EURO LOCKSHIELD is a lockshield valve designed primarily for TRVs and TRV packs.




EV10LAN

Lockshield valves help to keep the heating system balanced by controlling the flow of water, ensuring all radiators heat up at the same time. EURO LOCKSHIELD valves come in 10mm and 15mm sizes with drain off options available and are finished in nickel.

Dimensions

EURO LOCKSHIELD


10/15mm Angle



Model	A	B	C
	(mm)	(mm)	(mm)
10/15mm Angle	19.0	28.0	57.0

EURO LOCKSHIELD with Drain Off

10/15mm Angle



Model	A	B	C	D
	(mm)	(mm)	(mm)	(mm)
10/15mm Angle/Drain	19.0	28.0	57.0	23.0

NB: All measurements are nominal.

General specification



CERTIFICATION
Produced under a quality management system - ISO 9001:2008.



OPERATING PRESSURES
Tested to a maximum pressure of 10 bar. Pressure tested in accordance with BS 2767.



GUARANTEE
2 year guarantee from date of purchase against manufacturing defects.



OPERATING TEMPERATURE
Maximum 120°C.



COLOUR
Finished in nickel.



DELIVERY
2 - 5 working days.



CONNECTIONS
Compression.

For more general information, please see page 260.



EV10LAND

EURO LOCKSHIELD

Description	Metal Finish	Order Code	Minimum Order Qty
10mm Angle	Nickel	EV10LAN	10
10mm Angle with Drain Off	Nickel	EV10LAND	10
15mm Angle	Nickel	EV15LAN	10
15mm Angle with Drain Off	Nickel	EV15LAND	10










DECORATIVE

MYSON offer a selection of DECORATIVE valves for projects that need that extra special finishing touch.



Manufactured from solid brass, they are beautifully finished in highly polished chrome. The range includes compression and screwed iron connections, with straight and angle options available.

General specification


- 
CERTIFICATION
 Produced under a quality management system - ISO 9001:2008. Conforms to BS 2767-10.
- 
GUARANTEE
 2 year guarantee from date of purchase against manufacturing defects.
- 
COLOUR
 Finished in polished chrome.
- 
CONNECTIONS
 Compression or screwed iron.
- 
OPERATING PRESSURES
 Tested to a maximum pressure of 10 bar.
- 
OPERATING TEMPERATURE
 Maximum 120°C.
- 
DELIVERY
 2 - 5 working days.

For more general information, please see page 260.


Dimensions

Handwheel


15mm or 1/2" BSP Angle



15mm or 1/2" BSP Straight (for vertical mounting)




15mm or 1/2" BSP Straight (for horizontal mounting)




Model	A	B	C	D
	(mm)	(mm)	(mm)	(mm)
15mm or 1/2" BSP Angle	65.0	41.0	55.0	60.0
15mm or 1/2" BSP Straight (Vert)	74.0	40.0	71.0	60.0
15mm or 1/2" BSP Straight (Horiz)	74.0	49.0	56.0	60.0

Lockshield


15mm or 1/2" BSP Angle



15mm or 1/2" BSP Straight (for vertical mounting)



15mm or 1/2" BSP Straight (for horizontal mounting)



Model	A	B	C	D
	(mm)	(mm)	(mm)	(mm)
15mm or 1/2" BSP Angle	54.0	41.0	55.0	26.0
15mm or 1/2" BSP Straight (Vert)	61.0	40.0	71.0	26.0
15mm or 1/2" BSP Straight (Horiz)	61.0	49.0	56.0	26.0

NB: All measurements are nominal.



DEC15SHC



DEC15LAC

DECORATIVE

Description	Metal Finish	Order Code	Minimum Order Qty
15mm or 1/2" BSP Angle Handwheel	Polished Chrome	DEC15HAC	1
15mm or 1/2" BSP Angle Lockshield	Polished Chrome	DEC15LAC	1
15mm or 1/2" BSP Straight Handwheel (for Vertical Mounting)	Polished Chrome	DEC15HVC	1
15mm or 1/2" BSP Straight Handwheel (for Horizontal Mounting)	Polished Chrome	DEC15SHC	1
15mm or 1/2" BSP Straight Lockshield (for Vertical Mounting)	Polished Chrome	DEC15LVC	1
15mm or 1/2" BSP Straight Lockshield (for Horizontal Mounting)	Polished Chrome	DEC15LHC	1
Pipe Sleeve Kit 180mm	Polished Chrome	DEC180SLV	1