



REMOTE THERMOSTATS & ACCESSORIES

2TRVRSHEAD2

The MYSON remote sensor incorporates a traditional TRV head which can be set to the desired temperature. The room temperature is monitored via a 2, 5 or 10 metre capillary connected to the sensing element which can be mounted in a convenient and temperature representative area of the room. Remote sensor heads are ideal for use when it is difficult for a traditional TRV to operate, such as behind furniture or in direct sunlight, and are primarily used with LST radiators.

We also have a large range of accessories for TRVs, including our unique impaired dexterity TRV head, ideal for care homes and nursing homes.



2TRVHEADDEX

DIMENSIONS

Remote Adjuster

Model	A (mm)	B (mm)	C (mm)	D (mm)
2/5m Capillary	53.5	32.5	80.0	80.0

Remote Sensor

Model	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)
2/5/10m Capillary	28.0	112.0	50.0	28.0	90.0

NB: All measurements are nominal.

GENERAL SPECIFICATION

- ✓
CERTIFICATION
 Produced under a quality management system - ISO 9001:2008.
- 2
GUARANTEE
 2 year guarantee from date of purchase against manufacturing defects.
- 🚚
DELIVERY
 2 - 5 working days.

For more general information, please see page 250.



Description	Order Code	Minimum Order Qty
Remote Sensor 2m Capillary	2TRVRSHEAD2	1
Remote Sensor 5m Capillary	2TRVRSHEAD5	1
Remote Sensor 10m Capillary (special order)	2TRVRSHEAD10	1
Remote Adjuster 2m Capillary	2TRVADJHEAD2	1
Remote Adjuster 5m Capillary	2TRVADJHEAD5	1
Standard TRV Head Only	2TRVHEAD	1
PETITE TRV Head Only	PETTRVHEAD	1
Standard TRV Head 'Contract' Only	2TRVHEADCON	1
Theft Resistant Ring	2TRVRING	1
Theft Resistant Collar	2TRVCOLLAR	1
Commissioning Cap	2TRVCAP	1
Impaired Dexterity TRV Head Only	2TRVHEADDEX	1