



2TRV22AN

## TRV 2-WAY BODIES

MYSON offers a range of TRV bodies with sizes of 15mm & 22mm copper connections and ½" & ¾" iron pipe connections. All the TRV bodies conform to EN 215 and are available as angle, horizontal angle and straight. Finished in high quality nickel or chrome, all the TRV bodies are compatible with our range of remote sensors and TRV heads.



2TRV15IN

**DIMENSIONS**

**Standard/Straight Bodies**

15mm Standard

15mm & 1/2"/22mm & 3/4" Straight

Model	G	B	L	H*	h*
	(in)	(mm)	(mm)	(mm)	(mm)
15mm Standard	1/2	64.0	32.0	108.0	72.0
15mm & 1/2" Straight	1/2	95.0	33.0	113.0	77.0
22mm & 3/4" Straight	3/4	106.0	37.0	116.0	80.0

**Horizontal/Vertical Angle Bodies**

15mm & 1/2" Horizontal

15mm & 1/2"/22mm & 3/4" Vertical

Model	G	B	L	H*	h*
	(in)	(mm)	(mm)	(mm)	(mm)
15mm & 1/2" Horizontal	1/2	53.0	37.0	115.0	79.0
15mm & 1/2" Vertical	1/2	58.0	26.0	109.0	75.0
22mm & 3/4" Vertical	3/4	66.0	29.0	111.0	87.0

H\* Fitted with 2TRVHEAD or 2TRVRSHEAD  
h\* Fitted with 2TRVADJHEAD

NB: All measurements are nominal.

TRV head not included.

**GENERAL SPECIFICATION**

- ✓

**CERTIFICATION**  
Produced under a quality management system - ISO 9001:2008 and complies to EN 215-1.
- 2

**GUARANTEE**  
2 year guarantee from date of purchase against manufacturing defects.
- 🔧

**COLOUR**  
Finished in nickel or chrome plate.
- 🚚

**DELIVERY**  
2 - 5 working days.
- 🔥

**OPERATING PRESSURES**  
Tested to a maximum pressure of 10 bar.
- 🌡️

**OPERATING TEMPERATURE**  
Maximum 120°C.
- 🔌

**CONNECTIONS**  
Compression or pushfit.



For more general information, please see page 242.

Description	Metal Finish	Order Code	Minimum Order Qty
15mm & 1/2" Vertical Angle	Nickel	2TRV15AN	1
15mm & 1/2" Horizontal Angle	Nickel	2TRV15IN	1
15mm & 1/2" Straight	Nickel	2TRV15SN	1
15mm Standard TRV 2-WAY Body	Chrome	2TRVBOC	1
15mm Standard TRV 2-WAY Body	Nickel	2TRVBON	1
22mm & 3/4" Vertical Angle (one way flow)	Nickel	2TRV22AN	1
22mm & 3/4" Straight (one way flow)	Nickel	2TRV22SN	1